


# Tmetrics C20 3D Super EDF Microscope Camera


A smart camera that can directly obtain microscopic 3D images and measure them, upgrading your microscope's observation and analysis competence!



## 3D Super EDF Microscope Camera - Tmetrics C20

---

- **Easy to use:** No computer required, perform 3D observation and measurement
- **Wide applications:** equip with metallographic, stereo and other reflective microscopes.
- **Accuracy measurement:**  $\pm 2\mu\text{m}$  measuring accuracy for 2D&3D with 10x objective lens.




The C20 camera integrates features of high integration and flexibility, it can be directly used on reflective microscopes without any additional modification, the operation is easy to be done and all functions can be completed via mouse. Its built-in core technology can offer strong smart linkage performance guarantee for microscopic system: built-in intelligent heterogeneous host can replace computer to carry out plenty of calculating works directly, and the operation is speedy and stable. Real-time super depth of field and 3D moulding algorithm can contribute microscopic system to achieve comprehensive three-dimensional observation and measurement analysis. Meanwhile, the automatically edge recognition algorithm can also further improve the efficiency of microscopic observation and batch operation.

# Core technology creates a strong linkage performance

---


## ■ A Heterogeneous system

Possess ability for high speed data calculation



### ■ Three computing algorithms

- Super depth of field
- 3D moulding
- Edge recognition




## ■ Four in one systems

High-speed camera



Imaging analysis software



Z-axis motorize stage



High-performance host



## ■ Upgrading your microscope's capability


2D observation




Super depth of field



3D measurement




2D auto measurement



# Super depth of field to get all features on the same plane

Open "Capture-Advanced imaging-EDF&3D" function module in the software, confirm the position of the upper and lower focal planes to be observed in the image via mouse, click "EDF", then the C20 will automatically fulfill the depth of field, show all features on the image.




Before EDF




After EDF

## ■ Real-time EDF for clear microscopic observation

Ordinary microscopes cannot focus on multiple layers at the same time under high magnification. It is easy to cause angle deviation, rotation and uneven focal plane by using third party software and hardware systems to expand the depth of field. The C20 inner smart EDF algorithm can help solve these problems, capture a clear and correct full-frame focusing image.



The EDF image of third SW and HW system




The EDF image of C20

## ■ Real-time WDR to eliminate strong reflection

Strong reflections on the metal surface may lead to misjudgment of details. The C20 provide its WDR function to capture the perfect exposed images by calculating data in real time from multiple images of different brightness levels.





Before WDR




After WDR

# Create 3D matrix and easily measure any location

Open "Capture-Advanced imaging-EDF&3D" function module in the software, confirm the position of the upper and lower focal planes to be observed in the image via mouse,, and click "3D", then C20 will automatically complete 3D moulding. You can observe the real scene or pseudo-color model with 360° rotation.




The Real scene model




The pseudo-color model

## Rich 3D Measurement functions

The C20 provides a wealth of 3D tools for easily measure any position of the 3D model and record the data in real time. With the metallographic microscope of 10 times objective lens, , the Z-axis measurement accuracy and repeatability is  $\pm 2$  micron and  $\pm 1$  micron. The higher magnification objective lens, and the higher precision data.




### ■ The inner height measurement



Microscope: stereo  
Model: Clock gear  
Height: 5.661mm

### ■ The precision structure analysis




Microscope: metallographic  
Model: sensor chip  
Height: 34.062μm




## Automatic 2D measurement for your batch operations

The C20 also features 2D intelligent image recognition to help you quickly set up the standard measurement pattern without manual precise positioning, and finish various batch measurement operations. With the stereo microscope of 2.5 times magnifying, the 2D automatic measurement accuracy and repeatability is  $\pm 5$  micron and  $\pm 3$  micron.




- Quality judgment



For standard parts, C20 can automatically display OK/NG results of samples according to the set standard deviation range, improving the efficiency of quality detection.

- Batches tasks



For non-standard parts, C20 can output the measurement data of all samples at one time by setting the similarity tolerance to improve the efficiency of batch tasks.

## Report creation function of humanity

The C20 can not only save images and video data, but also automatically create test reports with pictures and texts, all 2D and 3D data in the work-flow all can be exported. The job was done when operation finished, easy and simple!



# Product specification


| Model                           | Tmetrics C20                  |   |
|---------------------------------|-------------------------------|---|
| Camera Features                 | Sensor                        | Sony 1/2"color CMOS   |
|                                 | Resolution                    | 1080P(1920×1080)  |
|                                 | Pixel size                    | 3.75μm×3.75μm   |
|                                 | Shutter mode                  | Rolling   |
|                                 | Scanning method               | Progressive scanning  |
|                                 | Frame rate                    | 60fps(Normal),30fps(WDR)  |
|                                 | Gain                          | Automatic / Manual  |
|                                 | Exposure time                 | Automatic: 0.1ms-16.6ms, manual: 0.0001s-1s   |
|                                 | White balance                 | Automatic/manual/area   |
|                                 | Image storage                 | TIFF/JPEG   |
|                                 | Video format                  | AVI/MP4(1080P)  |
| Advanced Features<br>(Embedded) | 3D noise reduction            | Support   |
|                                 | WDR                           | Support   |
|                                 | Real-time EDF                 | Support   |
|                                 | Edge enhancement              | Support   |
|                                 | Gamma correction (contrast)   | Support   |
|                                 | Color enhancement             | Support   |
|                                 | Flat field correction         | Support   |
|                                 | Effect mode                   | Normal/Negative/Relief/Grayscale  |
| 3D display and<br>measurement   | Online calibration            | Support   |
|                                 | 3D display                    | Pseudo-color/real scene display, grid lines, 360°rotation   |
|                                 | 3D histogram                  | Support   |
|                                 | 3D profile measurement        | Height difference, curvature, area, roughness   |
|                                 | 3D surface measurement        | Step height, volume, surface roughness  |
|                                 | Z range (depth of field)      | 23000μm   |
|                                 | 3D measurement accuracy (10X) | ±2μm  |
|                                 | 3D repeatability (10X)        | ±1μm  |
|                                 | 3D measurement report         | Support, editable template  |
| 2D measurement                  | 2D calibration ruler          | Support   |
|                                 | 2D manual measurement         | Point-point, point-line, line-line,Parallel, perpendicular, polygon, circle, arc, concentric circle, circle-circle, angle |
|                                 | Counter                       | Manual  |
|                                 | 2D measurement accuracy (10X) | ±2μm  |
|                                 | 2D repeatability (10X)        | ±2μm  |
|                                 | 2D measurement report         | Support   |
| Input                           | Mouse input                   | USB mouse   |
|                                 | Keyboard input                | USB keyboard  |
| Interface                       | Optics                        | Standard C-Mount  |
|                                 | Video                         | HDMI 2.0  |
|                                 | Internet connection           | Fast Ethernet   |
|                                 | USB                           | USB2.0 x 3, USB3.0 x1   |
| Others                          | Storage capacity              | Built-in 32G Emmc   |
|                                 | Power supply                  | 12V 8A  |
|                                 | Weight                        | 2.5kg   |
|                                 | Appearance size (WxHxD)       | 87cm*181cm*103cm  |
|                                 | Working environment           | 5℃-40℃ (temperature), 45%-85% (humidity)  |

# Reference case and upgrade your microscope

---




## Material section analysis

---




## Surface trace detection

---








## Biology observation

---



## Component measurement

---



Singapore Main Office  
Telephone: +65 6996 0391  
Email: [info@simtrum.com](mailto:info@simtrum.com)

China Main Office  
Telephone: +86 1500853620  
Email: [eva.yang@simtrum.cn](mailto:eva.yang@simtrum.cn)

**SIMTRUM**  
[www.simtrum.com](http://www.simtrum.com)